

mC30

from 40 mm



For the most convenient inspection in or around the house

The mC30 enables an easy inspection of pipes. Perfect for the inspection of all pipes for residential areas.

mC30

- Pipe diameter from 40 mm
- 29 mm axial camera with permanent upright image/self-leveling
- 30 m flexible push cable
- 90° bends from 50 mm
- Sunlight-readable 7"-display
- Battery life of 2 – 3 hours

mC50 • Duo

from 70 mm

from 40 mm



Comfortable Inspection

With the mC50 you perform a comfortable inspection of pipes.

mC50

- Pipe diameter from 70 mm
- 55 mm axial camera with permanent upright image/self-leveling
- 60 m flexible push cable
- 90° bends from 80 mm
- Sunlight-readable 8"-display
- Battery life of 2 – 3 hours

mC50 Duo

- Pipe diameter from 40 mm
- 29 / 55 mm axial camera with permanent upright image/self-leveling
- 20 / 60 m flexible push cable
- 90° bends from 50 mm
- Control unit with function keys and variable light regulation
- Sunlight-readable 8"-display
- Battery life of 2 – 3 hours

mC80

from 70 mm



Push System

The standard push cable length of the mC80 is 130 m and assures a very comfortable manhole-to-manhole pipe inspection for pipes diameter from 70 mm.

- Pipe diameter from 70 mm
- 55 mm axial camera with permanent upright image/self-leveling
- 130 m flexible push cable
- 90° bends from 100 mm
- Sunlight-readable 8"-display
- Battery life of 2 – 3 hours

mC360

from 70 mm



Pan & Tilt Camera Inspection System

With our intelligent pan & tilt camera inspection system you will reach easily even the remotest corner. The mC360 is one of the smallest cameras in this segment, pipes from 70 mm diameter can be inspected.

- Pipe diameter from 80 mm
- Pan & Tilt colour camera head with 50 mm diameter
- 60 m flexible push cable
- 90° bends from 80 mm
- Sunlight-readable 8"-display with text generator
- Compatible with axial camera heads

RAUSCH

VISION MEETS PRECISION

mC360 compact

from 70 mm



Compact Pan & Tilt Camera Inspection System

This compact inspection system enables the entry into the camera head technology. The compact all-rounder allows inspection with the pan & tilt camera SK50. With one of the smallest pan and tilt cameras on the market, even the most remote corners can be examined.

- Pan & tilt camera head with 50 mm diameter
- 40 m flexible push cable
- 90° bends from 80 mm
- Sunlight-readable 7"-display

minCord 5

from 15 mm



Small and compact: Designed to reach even the most difficult-to-reach places

The non-destructively inspection enables you to inspect even the tightest spaces and saving costly disassembles. Tubes, cavities, welding seams, turbines, hollow profiles and castings. At the same time, the cameras are so robust that they can easily withstand the harsh field conditions. In this way you locate all surface damages, cracks, sediments and deteriorations with minimal effort.

- 13 mm axial camera
- 15 m flexible push cable
- 33 kHz / 512 Hz / 640 Hz locating sonde
- 90° bends from 25 mm
- Sunlight-readable 5"-display
- Battery life of 5 – 7 hours

minCord XL

from 15 mm



Inspection system for sewers

The mincord XL is used to inspect pipes ranging from 15 mm diameters. The complete camera system ensures an optimum view. Individual applications in buildings and industry.

- 13 / 18 mm axial camera
- 30 m flexible push cable
- 33 kHz / 512 Hz / 640 Hz locating sonde
- 90° bends from 25 mm
- Sunlight-readable 7"-display
- Battery life of 5 – 7 hours

Axialcameras from 15 mm

KK13

Application range from 15 mm
Diameter of 13 mm
Pressure-tight up to 1 bar
Location sonde with
33 kHz / 512 Hz / 640 Hz

KK18

Application range from 25 mm
Diameter of 18 mm
Pressure-tight up to 1 bar
Location sonde with
33 kHz / 512 Hz / 640 Hz

KK29


Application range from 40 mm
Diameter of 29 mm
Pressure-tight up to 10 bar
Upright image (self-leveling)
Location sonde with 33 kHz / 512 Hz

KK55

Application range from 70 mm
Diameter of 55 mm
Pressure-tight up to 10 bar
Upright image (self-leveling)
Location sonde with 33 kHz / 512 Hz

SK50

Pan & Tilt camera with high resolution colour camera module, Diameter of 55 mm
For pipes 70 mm and larger
Pressure-tight up to 6 bar



Rausch Viewer App

User interface of viewer app for recording of photos and videos including text generator.

RAUSCH

STRONG TECHNOLOGIES. FOR A CLEAN ENVIRONMENT.

Rausch GmbH

Bruehlmoosweg 40
88138 Weissensberg
Ph. +49 8389 898-0
sales@rausch.international

Service Rausch GmbH

Bruehlmoosweg 40
88138 Weissensberg
Ph. +49 8389 898 - 111
service@rausch.international

Rausch Electronics GmbH

Konrad-Zuse-Straße 4
87509 Immenstadt
Ph. +49 8323 99470 0
sales-re@rausch.international

Service Rausch Electronics GmbH

Konrad-Zuse-Straße 4
87509 Immenstadt
Ph. +49 8323 99470 0
service-re@rausch.international

2026/1

www.rausch.international/en

